



# Clicwall® FR

## Decorative wallcovering, fire retardant

Melamine faced fire-retardant and non-structural MDF-LA FR board with Uniclic profile, available in an extensive range of high-quality Unilin Evola designs. Clicwall FR is suitable for dry conditions, service class 1, mainly used for separation walls and wall linings. This fire-retardant product is B-s1,d0 certified. Clicwall FR is made from 100% recovered wood.

### Applications

- Separation walls
- Wall linings

### Characteristics

-  MDF-LA FR (EN 14322)
-  A wide selection of designs
-  Perfect for intensive use
-  Quick installation for an immediate stylish result
-  Fire retardant
-  Tongue and groove
-  100% recovered wood



## Applications

Melamine faced, fire retardant and non-structural MDF board for separation walls and wall linings. Long sides provided with Uniclic profile resulting in a fast and easy click system. Scratch resistant, impact proof and highly hygienic which makes Clicwall FR suitable for projects in retail, hotel, holiday homes, modular units, office, senior homes, education, etc. Clicwall FR can be used in non humid conditions (service class 1). Clicwall FR 12 mm (thickness) is conform Euroclass B-s1,d0; 10mm results in Euroclass B-s2,d0.

## Available dimensions and thicknesses

Dimensions: Net/gross (HxWxD):

- Clicwall FR standard B-s1,d0 : 2785x600x12mm / 2785x618x12mm; 15,5kg
- Clicwall FR standard B-s2,d0 : 2785x600x10mm / 2785x618x10mm; 13kg

Other dimensions: on request.

## Certificates

Unilin Panels is actively committed to sustainable forest management. Clicwall FR is standard PEFC labelled and is available on demand with FSC labeling.

Clicwall FR is Cradle to Cradle<sup>®</sup> Material Health V4.0 Certified, meeting strict criteria for material safety and sustainability.

Carb II / TSCA VI compliant.