



# Clicwall<sup>®</sup> MR

Decorative wallcovering, moisture resistant.

Melamine faced moisture-resistant and non-structural MDF.H board with Uniclic profile, available in an extensive range of high-quality UNILIN-Evola designs. Clicwall MR is suitable for humid conditions, service class 2, mainly used for separation walls and wall linings. Clicwall MR is made from 100% recovered wood.

## Applications

- Separation walls
- Wall linings

## Characteristics



MDF.H (EN 14322)



A wide selection of designs



Perfect for intensive use



Quick installation for an immediate stylish result



Tongue and groove



100% recovered wood



# Clicwall<sup>®</sup> MR

## Applications

Melamine faced, moisture resistant and non-structural MDF board for separation walls and wall linings.

Long sides provided with Uniclic profile resulting in a fast and easy click system.

Scratch resistant, impact proof and highly hygienic which makes Clicwall MR suitable for projects in retail, hotel, holiday homes, modular units, office, senior homes, education, etc.

Clicwall MR is conform Euroclass D-s2,d0 (non fire retardant application) and can be used in humid conditions (service class 2).

## Available dimensions / thicknesses

Dimensions: Net/gross (HxWxD):

- Clicwall standard: 2785x600x10mm / 2785x618x10mm; 13kg/panel

Other dimensions: on request

## Certificates

UNILIN Division Panels is actively committed to sustainable forest management. Clicwall MR is standard PEFC labelled and is available on demand with FSC labeling.

Carb II / TSCA VI on demand.